

GROOVED & FLANGED WHEELS



Designed for use on rails (generally channel or inverted angle iron) for production lines and other layouts demanding set routes. The grooves are fully machined. V grooved wheels run equally well on ordinary floors on the flat tread sides incorporated for this purpose. F-Flange wheels on flat or square tracks

WHEEL DIAMETER mm	TREAD WIDTH mm	CAPACITY KG	FLANGE OR GROOVE	HUB WIDTH	BORE DIA.	REF.	BEARINGS TO BE FITTED INSIDE THE WHEEL
75	35	205	25	45	19.05/25	075 CWR/V	BEARING SELECTION ROLLER SUFFIX RB PRECISION SUFFIX BB
100	46	250	25	60	19.05/25	100 CWR/V	
	33	250	13	50	19.05/25	100 CWR/F	
125	38	265	25	60	19.05/25	125 CWR/V	
150	35	910	13	60	19.05/25	150 CWR/F	
	44	910	32	50	19.05/25	150 CWR/V	

SPLIT DISC WHEELS

Nylon & Steel Centres



Wheel diam: 150mm - 400mm

Capacity: 70kg - 200kg

WHEEL DIAMETER mm	TREAD WIDTH mm	CAPACITY KG	BORE DIA.	STEEL REF.	NYLON REF.	BEARINGS ADD SUFFIX		
						NYLON BUSH	ROLLER	PRECISION BALL
150	50	70	25	WSS062	WSN062	P	R	B
200	50	100	25	WSS082	WSN082	P	R	B
250	50	115	25	WSS102		P	R	B
300	50	125	25	WSS122		P	R	
350	75	180	25	WSS143		P	R	B
	100	200	25	WSS144		P	R	B
400	75	200	25	WSS164		P	R	B

