



SOLID RUBBER WHEELS

Wheel diam: 75mm - 250mm
Capacity: 60kg - 250kg

Quiet running, good floor protection & low abrasion resistance. Suitable for general purpose applications where duty is not too high. Wheels are not oil resistant & can wear out quickly on rough floors.



WHEEL DIAMETER mm	TREAD WIDTH mm	CAPACITY KG	HUB LENGTH	BORE DIAMETER	REF.
75	32	60	39	12.7	WRH3
100	38	95	46	14.3	WRH4
	50	120	60	25/19.05	WSR042
125	42	150	46	14.3	WRH5
	50	150	60	25/19.05	WSR052
150	50	180	60	25/19.05	WRH6
200	50	200	60	25/19.05	WSR082
250	50	250	60	25	WSR102
350	75	250		25	WSR143

HEAVY DUTY CUSHIONED TYRES

Wheel diam: 400MM
Capacity: 800kg - 1044kg

WHEEL DIAMETER mm	TREAD WIDTH mm	LOAD CAPACITY		BORE DIAMETER	REF.	BEARINGS ADD SUFFIX	
		20 KPH	10 KPH			PRECI-SION BALL	TAPER ROLLER
400	100	800	1044	25	HG 57CT	B	TR
	100	800	1044	30	HG 20CT	B	TR

